

MORTAR MIXERS

ASE MIX 15 ASE MIX 35



19



ASE MIX 15 and ASE MIX 35 are designed for mixing special materials such as grouting, refractory, masonry, filling, injecting mortars, etc.

It homogeneously mixes any dry pre-mixed factory-made materials or mortars to be prepared in the site with water and makes them ready to be used.

ASE MIX 15 S model has an automatic water feeding system. Water is fed into the mixer at quantities specified on the digital indicator thanks to the pulse water meter.

It's possible to continue the water feeding through the manual button in case of additional water requirement.

In ASE MIX 35, materials mixed with water are discharged at desired quantities rapidly and without loss thanks to its slide on the front side.

TECHNICAL DATA

	MIX 15	MIX 35
Mixing capacity*	50-200 l/min	90 l/min
Power supply	400 V, 50 Hz	400 V, 50 Hz
Fuse protection	3x25 A	3x25 A
Mixer motor	3,0 kW	3,0 kW
Speed of motor	55 rpm	20-60 rpm
Hopper content	160 l	150 l
Loading height	1150 mm	adjustable
Power cable	5x4 mm ²	5x4 mm ²
Length	2500 mm	1900 m
Width	1200 mm	670 mm
Height	1215 mm	940 m
Total weight approx.	210 kg	140 kg

* Depending on motor speed, mortar quality, composition and consistency, type of the mixing paddle.

FIELDS OF APPLICATION

For all lime- or cement-based ready-mixed dry mortars and construction site mixes, such as:

- Grouting mortars
- Refractory mortars
- Injection mortars
- Masonry mortars
- Light concrete mortars
- Reinforcing mortars
- Decorative renders
- Cement renders
- Lime renders
- Insulating renders
- Floor screed mortars
- Scratch coat renders
- Levelling compounds
- Restoration renders
- Bonding mortars
- Facing renders
- Tilling and jointing mortars

... and many more

STANDARD EQUIPMENT

- Geared motor 3,0 kW
- Integrated control box
- Centrifugal water pump 1 HP (S)
- Water hose 1" 5 m with check valve and filter (S)
- Pulse water meter (S)
- Power cable 5x2,5 mm² 25 m CEE cpl. 32 A
- Shifting spanner
- 6/125 screwdriver